

8000 GPD INDUSTRIAL RO



SPECIFICATIONS

System	Brackish Water
Performance @ 25°C, 2000ppm TDS*	
Feed flow	4.0 m ³ /hr
Permeate flow	1.20 m ³ /hr
Recovery	Up to 50%
Rejection	95 - 98%
Operating pressure	200 psi max
Inlet pressure	40 - 90 psi max
Temperature	45°C max
Membrane housing	4 x 4040 Fibreglass
Membrane	4 x RE-4040-BE CSM
Pump & Motor	Grundfos CR1-23 X-P-A-E HQQE 2.2 kw 240V 50 hz
Piping	High pressure reinforced
Electrical	1.65 m power cord with 15A plug
Controller	ROC 2315 Microprocessor
Frame	Stainless Steel
Connections	1 1/4" Inlet, 1" M Concentrate, 1" M Permeate & 1/2" M Comp Brine
Dimensions	1420 H x 950 W x 1030 D

*NOTE – Performance will vary depending on raw water quality and temperature. Based on membrane manufacturers recommendations and are approx.

FEATURES

- Concentrate Flow Meter – 1-10GPM (35 lpm)
- Permeate Flow Meter – 1-10GPM (35 lpm)
- Recycle Flow Meter – 1-5GPM (18 lpm)
- Source Water Pressure Gauge – 0-200PSI
- RO Outlet Water Pressure Gauge – 0-500PSI
- Low Pressure Switch
- 1" Inlet Actuator
- 1/2" Flush Solenoid Valve
- Recycle 1/2" Stainless Steel Gate Valve
- Concentrate 1/2" Stainless Steel Gate Valve
- Check Valve in Recycle Valve
- Power On/Off Switch
- Provisions for a Float Switch (Not supplied)

ROC 2315 FEATURES

- Temperature monitoring
- Conductivity monitoring with over limit alarm
- Adjustable Flush Time sequence
- TDS monitoring
- Indicator lights for
 - Low Feed Pressure
 - Low Pressure
 - High Pressure
 - Tank Full
 - Auto Flush
- 3 1/2" LED digital display